

## 9003 – Animated Castle (aluminium or wood)



MATERIALS	ALUMINIUM TIMBER
DIMENSIONS	400X433X397 CM
DECKS HEIGHT	84 - 140 CM
CRITICAL FALL HEIGHT	140 CM
MINIMUM SPACE REQUIRED	742X709 CM
SAFETY FLOOR REQUIRED	38 MQ

Certified according to European Standard EN 1176.

Component list:

- N.8 structural poles:

**ALUMINIUM** in league of aluminium with a cross section of 90x90 mm and 3 mm thick, rounded on each side to avoid dangerous edges and provided of COVER-POLE of superior shape closing squared with rounded corners.

**WOOD** - in northern pine of first choice structural poles with fine and compact grain, seasoned for 12 months with 8 weeks rest following pressure treatment, of section 90x90 mm with rounded corners and rounded edges with a 4 leaf clover profile, fitted with a colored polyethylene cap.

- N. 3 decks: ALUMINIUM – composed by a plate from steel ashlar-work footboard 3 mm thick zincified; the four sides are extracted from the folding of the plate itself forming a 7cm border under the two footboards and 4 cm under the bridge of connection; the grained allows a perfect anti-slip effect.

WOOD: deck realized with northern pine boards.

- N.1 bridge of connection with polyethylene handrail 19mm thick and lateral rounded board of plugging in colored polyethylene 15mm thick.

- N.1 stair manufactured with 19 mm thick polyethylene sides and elements of climb (steps) made in steel ashlar-work and painted for outsides.

- N.2 rotational roofs in polyethylene.

- N.4 two-tone polyethylene panels 19mm thick moulded with decorative and available incisions in the following colors: yellow, blue, red UV stable.

- N.1 tube slide manufactured from rotationally moulded high density polyethylene in various UV stable colors and with a polyethylene entrance panel.

**Dimensions: 3999x4328xH3968 mm.**

**Minimum space required: 7420x7094 mm**

